BIOGUARD

The Bioguard Moisture Meter is a new generation of digital moisture meters that operates using high frequency measurement, compression of the sample and automatic temperature compensation for more reliable results.

MOISTURE ANALYSERS

FOR BIOFUELS

FOR

WOOD PELLETS

AND

SAWDUST



THE PORTABLE BIO MOISTURE METER
THAT YOU CAN RELY ON



Super Tech





MOISTURE ANALYSERS

FOR BIOFUELS

FOR

WOOD **PELLETS**

AND

SAWDUST

BIOGUARD

Additional advantages:

- Calibration for wood pellets and sawdust from both hardwood and softwood
- Digital readout with accuracy to one decimal point
- Combined test cell and compression unit
- Automatic temperature compensation
- Measuring cell made of polished aluminum
- Backlight display
- Casing made of shockproof ABS plastic
- Automatic calculation of average value
- Individual calibration for all bio types
- Can be updated with new moisture scales
- Supplied in shockproof transport case
- 2 year guarantee

The Bioguard Moisture Meter: Simple to use in four easy steps:



- Turn on the tester Fill the test cell. by pressing the ON/TEST button.
- Use the arrow keys to select bio fuel type.





 Screw on lid until the pressure indicator is level with the top of the lid.



Press the ON/TEST button and read the moisture content directly from the display.

TECHNCIAL SPECIFICATIONS

- Measuring range (Moisture): 4.5% to 67% depending of biofuel type
- ◆ Operation range (Temperature):0 to 50 °C
- ♦ Resolution: 0.1% moisture
- ▲ Temperature compensation: Automatic
- ♦ Dimensions: 13 x 21 x 8 cm
- Weight including suitcase: 1.6 kg.
- Battery: 9 V Alkaline
- Display: Digital two line with backlight



We reserve the right to technical changes.